

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED206-109-6D-N1



Indoor, Six Digits. Visible up to 90 Feet Away Dimensions: 16"L x 4"H x 2.25"D Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- Counts by "1" / Reset to "0"
- Dimensions: 16"L x 4"H x 2.25"D
- 2.25" LED Display with Six Digits
- Counter will advance by one with a contact closure, and reset to "0" another.
- Mounting Brackets
- Complete Instructions

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED206-109-6D-N1 Specifications

Electrical Specifications

| | |
|-------------------|-----------------------|
| Power Source | 120VAC @ 60Hz. |
| Power Consumption | Max. 12 Watts |
| Current Draw | Typical 500 Amp |
| Power Cord Length | 10 Foot Business Plug |

Physical Specifications

| | |
|----------------------------|---|
| Indoor / Outdoor | Designed to be installed and viewed indoor |
| Operating Environment | 32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity |
| Dimensions | 16"L x 4" H x 2.25"D |
| Weight | Approx. 10 Lbs. |
| Number of Digits | Six (6) Digits |
| Character Height | 2.25" High Numbers |
| Viewing Distance | Up to 100 Feet Away |
| LED Color / Material | Red |
| LED intensity | 10 MCD Super-Bright Discrete LEDS |
| Power Supply | Yes |
| Enclosure Color / Material | Black Aluminum |
| Enclosure NEMA Rating | NEMA 1 Rated / NEMA 12 optional |
| Mounting Method | Two Mounting Brackets Included for Hanging / Wall Mount |
| Limited Warranty | One-Year Factory Service |