

***ELECTRONIC DISPLAYS INC.***

***www.electronicdisplays.com***



## **ED600D-109-4D-N1**



Visible up to 280 Feet Away. Dimensions: 26"L x 9.4"H x 2.5"D Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- Counts By "1" / Reset to "0"
- Dimensions: 26"L x 9.4"H x 2.5"D
- 6" Display with Four Digits
- Counter will advance by one with a contact closure, and reset to "0" with another.
- Mounting Brackets
- Complete Instructions

### **Contact EDI Today**

For further information visit our website [www.electronicdisplays.com](http://www.electronicdisplays.com) or call us at 1-800-367-6056 and contact a sales representative.

**Henry Bilitzki x 305 | Dennis Holmberg x 306**

Or email us at [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

# ED600D-109-4D-N1 Specifications

## Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 800 Amp
Power Cord Length	10 Foot Business Plug

## Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	26"L x 9.4" H x 3"D
Weight	Approx. 15 Lbs.
Number of Digits	Four (4) Digits
Character Height	6.0" High Numbers
Viewing Distance	Up to 280 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service