

www.electronicdisplays.com



ED406-109-6D-N1



Indoor, Six Digit. Viewable up to 200 Feet Away Dimensions: 26"L x 8"H x 2.25"D Display realtime information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- Counts by "1" / Reset to "0"
- Dimensions: 26"L x 8"H x 2.25"D
- 4" LED Display with Six Digits

Contact EDI Today

For further information visit our website <u>www.electronicdisplays.com</u> or call us at 1-800-367-6056 and contact a sales representative. **Henry Bilitzki x 305 | Dennis Holmberg x 306** Or email us at <u>ledsales@electronicdisplays.com</u>

ED406-109-6D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 12 Watts
Current Draw	Typical 900 Amp
Power Cord Length	6 Foot Business Plug

Operational Specifications

Data Input	Two momentary contact closures - increment and reset to "0"
Contract Closure	5 to 24VDC "Wet" or "Dry" Contact Closures (2)

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	26"L x 8" H x 3"D
Weight	Approx. 8 Lbs.
Number of Digits	Six (6) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 190 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service