

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED050-I-2011-N1-BCD



Displays are used to loaded status messages for the production lines. Customer selected messages will be triggered by BCD to display machine status or part status.

- 2" high alphanumeric text.
- Visible up to 90 feet
- Dimensions: 43" x 4" x 2.5"
- Displays are used to loaded status messages for the production lines.
- Select your messages by triggering by BCD to display machine status or part status.
- The display will accept preloaded serial messages form the supplied windows software application.
- 4 inputs inside the enclosure will activate each of the messages using BCD format. Up to 15 messages can be stored and activated using BCD.

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED050-I-2011-N1-BCD Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 20 Watts
Current Draw	Typical 700 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	43"L x 4"H x 2.5"D
Weight	Approx. 15 Lbs.
Number of Digits	20 Characters Viewable
Character Height	2.0" High Characters
Viewing Distance	Up to 100 Feet Away
LED Color / Material	Red, Green, Amber
LED intensity	10 MCD Blocks (5 x 7)
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 Optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service