ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED050-I-2411-N1



Dimensions: 52" L x 4" H x 2.5" D. Displaying information to employees is key to communicating ideas and goals and making decisions. Our industrial line of scrolling message signs is an excellent way to keep workers in touch with the ever-changing industrial environment. Message marquees can interface with PLC's, PC's and Embedded Controllers. We can provide the ASCII commands that will allow you to add data strings to virtually any software code.

- 2" High Alphanumeric Characters
- Red text (green / amber available)
- Visible up to 90 feet
- Enclosure: 52" x 4" x 2.5"
- Mounting Brackets
- Complete Instructions
- Factory Service One-Year Warranty on Parts and Labor
- Free MessagePro software included to create and send messages
- RS232 or RS422 Serial communication standard
- Ethernet communication optional with our ED2150 device

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED050-I-2411-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 20 Watts- All LEDS On
Current Draw	Typical 700 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	52" L x 4" H x 2.5" D
Weight	Approx. 20 Lbs.
Number of Digits	24 Characters Viewable
Character Height	2.0" High Characters
Viewing Distance	Up to 90 Feet Away
LED Color / Material	Red (Standard), Optional: Green Amber, Blue
LED intensity	10 MCD Blocks (5 x 7)
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 Optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service