

***ELECTRONIC DISPLAYS INC.***

[www.electronicdisplays.com](http://www.electronicdisplays.com)



## 6-2-V-A-3L



Display time / location and date. The horizontal series time zone displays have bar segment time displays with a ten-character dot matrix digital zone label below. The digital zone labels can hold any ASCII test string and is independent of the time zone parameters. Every display includes a high accuracy crystal oscillator and your choice of Ethernet, USB or RS232 interface for time zone parameter control

### Contact EDI Today

For further information visit our website [www.electronicdisplays.com](http://www.electronicdisplays.com) or call us at 1-800-367-6056 and contact a sales representative.

**Henry Bilitzki x 305 | Dennis Holmberg x 306**

Or email us at [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

## 6-2-V-A-3L Specifications

### Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 900 mA Per Field
Power Cord Length	6 Foot Business Plug

### Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	58"H x 15"W x 3"D
Weight	Approx. 45 Lbs.
Number of Fields	Six (6) Time Fields
Character Height	2.25" High Numbers
Viewing Distance	Up to 90 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service