

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED206-110-6D-N1-3INP



This display will increment / decrement and reset to "0". Three customer supplied momentary contact closures will control the counting and reset.

- Bright 2.25" High LED Display with Six Digits
- Dimensions: 16"L x 4"H x 2.25"D
- Up or Down Count by one. Counter will advance by one with a contact closure
Decrement by "one" with a contact closure
- Reset to "0" with another.

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED206-110-6D-N1-3INP Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 17 Watts
Current Draw	Typical 800 Amp
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	16"L x 4" H x 2.25"D
Weight	Approx. 8 Lbs.
Number of Digits	Six (6) Digits
Character Height	2.25" High Numbers
Viewing Distance	Up to 100 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service