

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED200-1605-N1



8" High Alphanumeric Text. 16 Visible Characters Per Line. Displaying information to employees is key to communicating ideas and goals and making decisions. Our industrial line of scrolling message signs is an excellent way to keep workers in touch with the ever-changing industrial environment. Message marquees can interface with PLC's, PC's and Embedded Controllers. We can provide the ASCII commands that will allow you to add data strings to virtually any software code.

- Indoor Static / Fixed Message Display
- 8" High Alphanumeric Text
- 16 Characters Visible At One Time
- Visible Up To 375 Feet
- Serial Input: RS232 / RS422 / Ethernet
- Dimensions: 104"L x 11.4"H x 3"D
- Power: 120VAC @ 60 Hz.
- 6-Foot Line Cord Provided
- Two Mounting Brackets
- Factory Service 1-Year Warrant

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED200-1605-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 35 Watts
Current Draw	Typical 5 Amp
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	104"L x 11.4"H x 3"D
Weight	Approx. 70 Lbs.
Number of Digits	16 Characters Viewable
Character Height	8.0" High Characters
Viewing Distance	Up to 375 Feet Away
LED Color / Material	Red (Standard), Optional: Green Amber, Blue
LED intensity	10 MCD Discrete LEDs
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service