

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



7-2-V-A-3L



Display time / location and date. The horizontal series time zone displays have bar segment time displays with a ten-character dot matrix digital zone label below. The digital zone labels can hold any ASCII test string and is independent of the time zone parameters. Every display includes a high accuracy crystal oscillator and your choice of Ethernet, USB or RS232 interface for time zone parameter control

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

7-2-V-A-3L Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 900 mA Per Field
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	69"H x 18"L x 3"D
Weight	Approx. 55 Lbs.
Number of Fields	Seven (7) Time Fields
Character Height	2.25" High Numbers
Viewing Distance	Up to 90 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service