### ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



## ED202-117-6D-N1



Indoor, Six Digit, Visible up to 90 Feet Away Dimensions: 16" L x 4" H x 2.25" D. Display real-time production information to your employees or customers. The display will receive an RS422/RS485 data signal from a PC / PLC and update the unit using standard ASCII protocol.

- Visible up to 90 feet
- RS485 Serial Input using Standard ASCII Characters
- Dimensions: 16" L x 4" H x 2.25" D
- Terminal Block to Wire in Two Customer Supplied Contacts (RX+/RX-)
- Mounting Brackets
- Factory Service One-Year Warranty on Parts and Labor
- Unlimited Technical Phone Support

### **Contact EDI Today**

For further information visit our website <a href="www.electronicdisplays.com">www.electronicdisplays.com</a> or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

# ED202-117-6D-N1 Specifications

### **Electrical Specifications**

Power Source	120VAC @ 60Hz.
	24VDC
	220VAC @ 50Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA
Power Cord Length	6 Foot Business Plug

### **Physical Specifications**

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	16" L x 4" H x 2.25" D
Weight	Approx. 6 Lbs.
Number of Digits	Six (6) Digits
Character Height	2.25" High Numbers
Viewing Distance	Up to 90 Feet Away
LED Color / Material	Red, Green, Amber, Blue, Tri-Color
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
	NEMA 12 Rated
	NEMA 4 Rated
	NEMA 4X Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service