

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED406-110-4D-N1



Indoor, 4 digit. Dimensions: 20"L x 8"H x 2.5"D Count up or down. Thumbwheel preset standard. Serial preset available. Two momentary inputs: increment/decrement by 1, preset to value. "Wet" or "Dry" contacts. Photo-eye, limit switch, etc. Ideal for assembly line production.

- Dimensions: 26"L x 8"H x 2.5"D
- Bright 4.0" High LED Display with Four Digits
- Counter will advance or decrement by "one" with a contact closure and preset to customer-defined number with another.
- Thumbwheels to preset the number.

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED406-110-4D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 700 Amp
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	20"L x 8" H x 2.5"D
Weight	Approx. 9 Lbs.
Number of Digits	Four (4) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 200 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDs
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service