

www.electronicdisplays.com



ED402-117-6D-N1



Indoor, Four Digit, Visible up to 190 Feet Away Dimensions: 26" L x 8" H x 2.25" D. Display realtime production information to your employees or customers. The display will receive an RS422/RS485 data signal from a PC / PLC and update the unit using standard ASCII protocol.

- Visible up to 190 feet
- RS485 Serial Input using Standard ASCII Characters
- Dimensions: 26" L x 8" H x 2.25" D
- Terminal Block to Wire in Two Customer Supplied Contacts (RX+ / RX-)
- Mounting Brackets
- Factory Service One-Year Warranty on Parts and Labor
- Unlimited Technical Phone Support

Contact EDI Today

For further information visit our website <u>www.electronicdisplays.com</u> or call us at 1-800-367-6056 and contact a sales representative. Henry Bilitzki x 305 | Dennis Holmberg x 306 Or email us at ledsales@electronicdisplays.com

ED402-117-6D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 700 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	26" L x 8" H x 2.25" D
Weight	Approx. 10 Lbs.
Number of Digits	Six (6) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 190 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 Rated Optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service