

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED206-104-4D-N1



Dimensions: 16" L x 4.0" H x 2.25" D. A 4-digit up and/or down timer with internal timing in MM:SS (minutes-seconds) or HH:MM (hours-minutes) format standard. Other time formats available. The display is preset via thumb wheel switches on the end plate or keypad remote (optional).

- Dimensions: 16" L x 4.0" H x 2.25" D
- Bright 2.25" High LED Display with Four Digits
- Four thumb-wheel switches on the end cap of the display allows time preset.
- Up-timer in MM:SS format will up-time or down-time by "one second " with a contact closure and preset to a customer-determined start point with another contact.
- Terminal Block to Wire in Customer Supplied Contacts
- Mounting Brackets
- Complete Instructions
- Optional Control Box w/ 10 Feet of Cable

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED206-104-4D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	16" L x 4.0" H x 2.25" D
Weight	Approx. 6 Lbs.
Number of Digits	Four (4) Digits
Character Height	2.25" High Numbers
Viewing Distance	Up to 100 Feet Away
LED Color / Material	Full Color
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service