

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED1200D-102-4D-N1



Dimensions: 52"L x 17.7"H x 2.25"D. Display real-time information to your employees or customers. The display will up-time in MM:SS (default) or HH:MM (select when ordering) when a customer-supplied on/off switch is activated. A separate momentary switch will reset the unit to "00:00".

- Dimensions: 52"L x 17.7"H x 2.25"D
- 12.0" LED Display with Four Digits
- MM:SS or HH:MM Format
- Up-timer will time up by one second / minute.
- Two Customer Supplied Contacts (Run/Hold & Reset)
- Two Mounting Brackets
- Complete Instructions

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at

1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED1200D-102-4D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	52" L x 17.7" H x 2.25" D
Weight	Approx. 35 Lbs.
Number of Digits	Four (4) Digits
Character Height	12.0" High Numbers
Viewing Distance	Up to 575 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDs
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service