

***ELECTRONIC DISPLAYS INC.***

*www.electronicdisplays.com*



## **ED1200-E-109-6D-N4**



Dimensions: 81" x 18.25" x 4" Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- 12" high numbers visible up to 575 feet
- Six digits using super-bright red LEDs for outdoor viewing
- Outdoor rated NEMA4 (standard) NEMA4X stainless steel enclosure (Optional)

### **Contact EDI Today**

For further information visit our website [www.electronicdisplays.com](http://www.electronicdisplays.com) or call us at 1-800-367-6056 and contact a sales representative.

**Henry Bilitzki x 305 | Dennis Holmberg x 306**

Or email us at [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

# ED1200-E-109-6D-N4 Specifications

## Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 20 Watts
Current Draw	Typical 900 Amp
Power Cord Length	Knockout for Conduit / 6 Foot Business Plug

## Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed outdoor
Operating Environment	10 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	81"L x 18.25" H x 4"D
Weight	Approx. 50 Lbs.
Number of Digits	Six (6) Digits
Character Height	12.0" High Numbers
Viewing Distance	Up to 575 Feet Away
LED Color / Material	Red LEXAN
LED intensity	2500 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 4 Rated / NEMA 4X optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service