

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED400D-E-102-4D-N4



An outdoor rated enclosure. 4" high numbers using outdoor LEDS. Display real-time information to your employees or customers. The display will up-time in MM:SS (default) or HH:MM (select when ordering) when a customer-supplied on/off switch is activated. A separate momentary switch will reset the unit to "00:00".

- 4" high numbers using superbright red LEDS. Four Digits in MM:SS format.
- NEMA4 Rated Outdoor Enclosure
- Up-timer in MM:SS (default) or HH:MM format (optional).
- Two Customer Supplied Contacts (Run/Hold & Reset)
- Viewable up to 200 Feet

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at

1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED400D-E-102-4D-N4 Specifications

Electrical Specifications

Power Source	<ul style="list-style-type: none">• 120VAC @ 60Hz.• 24VDC• 220VAC @ 50Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed outdoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	22" L x 11" H x 3" D
Weight	Approx. 20 Lbs.
Number of Digits	Four (4) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 200 Feet Away
LED Color / Material	Red, Green, Amber, Blue
LED intensity	10 MCD Super-Bright Discrete LEDs
Power Supply	Yes
Enclosure Color / Material	Black Aluminum Stainless Steel
Enclosure NEMA Rating	NEMA 4 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service