

***ELECTRONIC DISPLAYS INC.***

*www.electronicdisplays.com*



## ED600D-111-4D-N1



Up To 12 Digits Available. Indoor, 4- digit, Dimensions: 26" L x 9.4" H x 3" D. Display real-time production information to your employees or customers. The display will receive an RS232 data signal from a PC / PLC and update the unit using standard ASCII protocol.

- RS232 Serial Input using Standard ASCII Characters
- Dimensions: 26" L x 9.4" H x 3" D
- Terminal Block to Wire in Two Customer Supplied Contacts (RX+ / RX-)
- Mounting Brackets
- Complete Instructions (Download a .pdf)
- Factory Service One-Year Warranty on Parts and Labor
- Unlimited Technical Phone Support

### Contact EDI Today

For further information visit our website [www.electronicdisplays.com](http://www.electronicdisplays.com) or call us at 1-800-367-6056 and contact a sales representative.

**Henry Bilitzki x 305 | Dennis Holmberg x 306**

Or email us at [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

# ED600D-111-4D-N1 Specifications

## Electrical Specifications

Power Source	<ul style="list-style-type: none"> <li>• 120VAC @ 60Hz.</li> <li>• 24VDC</li> <li>• 220VAC @ 50Hz.</li> </ul>
Power Consumption	Max. 18 Watts
Current Draw	Typical 700 mA
Power Cord Length	6 Foot Business Plug

## Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	26" L x 9.4" H x 3" D
Weight	Approx. 25 Lbs.
Number of Digits	Four (4) Digits
Character Height	6.0" High Numbers
Viewing Distance	Up to 300 Feet Away
LED Color / Material	Red, Green, Amber, Blue, Tri-Color
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated NEMA 12 Rated NEMA 4 Rated NEMA 4X Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service