

***ELECTRONIC DISPLAYS INC.***

*www.electronicdisplays.com*



## ED600D-E-109-4D-N4



Dimensions: 28" L x 12" H x 4" D. Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- 6" High LED Display with Four Digits
- Visible up to 280 feet
- Super-bright red LEDs
- Outdoor NEMA4 rated enclosure. NEMA4X Stainless Steel Enclosure (Optional)

### Contact EDI Today

For further information visit our website [www.electronicdisplays.com](http://www.electronicdisplays.com) or call us at 1-800-367-6056 and contact a sales representative.

**Henry Bilitzki x 305 | Dennis Holmberg x 306**

Or email us at [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

# ED600D-E-109-4D-N4 Specifications

## Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 20 Watts
Current Draw	Typical 800 Amp
Power Cord Length	Knockout for Conduit / 6 Foot Business Plug

## Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed outdoor
Operating Environment	10 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	28"L x 12" H x 4"D
Weight	Approx. 30 Lbs.
Number of Digits	Four (4) Digits
Character Height	6.0" High Numbers
Viewing Distance	Up to 280 Feet Away
LED Color / Material	Red LEXAN
LED intensity	2500 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 4 Rated / NEMA 4X optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service