ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED202-111-4D-N1



Visible up to 90 feet. Dimensions: 12" L x 4" H x 2.25" D. Display real-time information to your employees or customers. The display will receive and display a standard ASCII protocol sent by a PC/PLC. Selectable baud rates, parity and data bits.

- RS232 Serial Input using Standard ASCII Characters
- Visible up to 90 feet
- Dimensions: 12" L x 4" H x 2.25" D
- Terminal Block to Wire in Two Customer Supplied Contacts (Data / Ground)
- Free MessagePro software to send data
- Mounting Brackets
- Complete Instructions (Download a .pdf)
- Factory Service One-Year Warranty on Parts and Labor
- Unlimited Technical Phone Support

Contact EDI Today

For further information visit our website <u>www.electronicdisplays.com</u> or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED202-111-4D-N1 Specifications

Electrical Specifications

Power Source	• 120VAC @ 60Hz.
	• 24VDC
	• 220VAC @ 50Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	12" L x 4" H x 2.25" D
Weight	Approx. 6 Lbs.
Number of Digits	Four (4) Digits
Character Height	2.25" High Numbers
Viewing Distance	Up to 90 Feet Away
LED Color / Material	Red, Green, Amber, Blue, Tri-Color
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 Optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service