

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED406-109-4D-N1



Viewable up to 200 Feet Away. Dimensions: 2"L x 8"H x 2.5"D Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- Counts By "1" / Reset to "0"
- Dimensions: 20"L x 8"H x 2.5"D
- 4" Display with Four Digits
- Counter will advance by one with a contact closure, and reset to "0" another.
- Mounting Brackets
- Complete Instructions

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED406-109-4D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 700 Amp
Power Cord Length	10 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	20"L x 8" H x 2.25"D
Weight	Approx. 8 Lbs.
Number of Digits	Four (4) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 200 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service