

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED402-EIP-4D-N1-CL



4"High Numbers Visible up to 190 feet 4 Digits in a Time Format EIP Input from a PLC EIP gateway included NEMA1 Aluminum Enclosure Power: 120VAC@60Hz or 24VDC

- 4"High Numbers
- Visible up to 190 feet
- 4 Digits in a Time Format
- EIP Input from a PLC
- EIP gateway inside the display - plug-n-run
- NEMA1 Aluminum Enclosure
- Power: 120VAC@60Hz or 24VDC

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED402-EIP-4D-N1-CL Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz. 24VDC 220VAC @ 50Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 600 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	20" L x 8" H x 2.25" D
Weight	Approx. 10 Lbs.
Number of Digits	Four (4) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 200 Feet Away
LED Color / Material	Red, Green, Amber, Blue, Tri-Color
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated NEMA 12 Rated NEMA 4 Rated NEMA 4X Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service