

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED406-110-4D-N1-3INP



Dimensions: 20" x 8" x 3". Features an increment input and a decrement input to display ACTUAL counts! The real-time nature of this display helps operators pace the line and meet goals. Display real-time production information to your employees or customers. The display will up count by one with a momentary switch. It will down-count by one when a customer-supplied momentary switch is activated. A separate momentary switch will reset the unit to "0". Three customer-supplied switch input (UP / DOWN / RESET TO "0").

- Bright 4.0" High LED Display with Four Digits
- Up or Down Count by one. Counter will advance by one with a contact closure, decrement by "one" with a contact closure and reset to "0" another.
- Terminal Block to Wire in Three Customer Supplied Contacts (UP / DOWN / RESET)
- Mounting Brackets
- Optional Control Box With 10 Feet of Cable

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED406-110-4D-N1-3INP Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 700 Amp
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	20"L x 8" H x 3"D
Weight	Approx. 9 Lbs.
Number of Digits	Four (4) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 200 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDs
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service