


ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED400D-E-109-6D-N4



Dimensions: 30" x 16" x 6" Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0". EDI also supplies an on-board 14VDC Power supply.

- 4" LED Display with Six Digits
- Super-bright red LEDs
- Visible up to 190 feet
- Outdoor NEMA4 or NEMA4X Stainless Steel Enclosure (Optional)

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED400D-E-109-6D-N4 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 20 Watts
Current Draw	Typical 700 Amp
Power Cord Length	Knockout for Conduit / 6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed outdoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	30"L x 16" H x 4"D
Weight	Approx. 25 Lbs.
Number of Digits	Six (6) Digits
Character Height	4.0" High Numbers
Viewing Distance	Up to 190 Feet Away
LED Color / Material	Red LEXAN
LED intensity	2500 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 4 Rated / NEMA 4X optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service