

***ELECTRONIC DISPLAYS INC.***

*www.electronicdisplays.com*



## ED1200D-109-4D-N1



Visible up to 575 Feet Away. Dimensions: 52"L x 17.7"H x 3.5"D Display real-time information to your employees or customers. The display will advance by "1" for every activation of a customer-supplied momentary switch. A separate momentary switch will reset the unit to "0".

EDI also supplies an on-board 14VDC Power supply.

- Counts By "1" / Reset to "0"
- Dimensions: 52"L x 17.7"H x 3"D
- 4" Display with Four Digits
- Counter will advance by one with a contact closure, and reset to "0" with another.
- Mounting Brackets
- Complete Instructions

### Contact EDI Today

For further information visit our website [www.electronicdisplays.com](http://www.electronicdisplays.com) or call us at 1-800-367-6056 and contact a sales representative.

**Henry Bilitzki x 305 | Dennis Holmberg x 306**

Or email us at [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

# ED1200D-109-4D-N1 Specifications

## Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 17 Watts
Current Draw	Typical 890 Amp
Power Cord Length	6 Foot Business Plug

## Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	52"L x 17.7" H x 3"D
Weight	Approx. 20 Lbs.
Number of Digits	Four (4) Digits
Character Height	12.0" High Numbers
Viewing Distance	Up to 575 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDs
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated / NEMA 12 optional
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service