

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED206-104-6D-N1



Dimensions: 20" L x 4" H x 2.25" D. Display real-time information to your employees or customers. The display will down-time in HH:MM:SS (default) when a customer-supplied on/off switch is activated. A separate momentary switch will reset the unit to "00:00:00. Keypad included to preset a time

- Dimensions: 20" L x 4" H x 2.25" D
- 2.25" LED Display with Six Digits
- HH:MM:SS (other time formats available)
- Two Customer Supplied Contacts (Run/Hold & Reset)
- Two Mounting Brackets
- Factory Service One-Year Warranty on Parts and Labor
- Preset with Keypad

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED206-104-6D-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	20" L x 4.0" H x 2.25" D
Weight	Approx. 8 Lbs.
Number of Digits	Six (6) Digits
Character Height	2.25" High Numbers
Viewing Distance	Up to 100 Feet Away
LED Color / Material	Full Color
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service