

ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED050-2005-2L-N1



2" High Alphanumeric Text. 20 Visible Characters Per Line. Displaying information to employees is key to communicating ideas and goals and making decisions. These message displays are an excellent way to keep workers in touch with the ever-changing industrial environment. Message marquee can interface with PLC's, PC's and Embedded Controllers. We can provide the ASCII commands that will allow you to add data strings to virtually any software code.

- Bright 2" High LED Sign
- 20 Alphanumeric Characters Per Line
- Visible Up To 90 Feet
- Dimensions: 43"L x 8"H x 3"D
- Static (Fixed)
- USB Connector & Terminal Block for Data Cables
- Mounting Brackets
- Factory Service 1-Year Warranty

Contact EDI Today

For further information visit our website www.electronicdisplays.com or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED050-2005-2L-N1 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 1 Amp
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoors
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	48"L x 8"H x 3"D
Weight	Approx. 30 Lbs.
Number of Digits	20 Characters Viewable
Character Height	2.0" High Characters
Viewing Distance	Up to 90 Feet Away
LED Color / Material	Red (Standard), Optional: Green Amber, Blue
LED intensity	10 MCD Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service