



## EDV111-1680-IND-N4/N4X-SO



**EDV111-32128-SO Shown**

- PLC Interface - Sample AOI's Provided.
- Built in EIP Gateway Device (ED3600) Included
- Optional PROFINET Ready (ED3600P Gateway Required)
- Single or Double Lines of Text
- Dimensions: 30.25"L x 10.25"H x 5"D
- 16 Rows of LEDS X 80 Columns of LEDS
- Bright, Monochrome red or amber LEDS
- 10 Foot, 120VAC @ 60Hz. Power Plug
- Two mounting tabs at the top of the enclosure
- Data Cable and Gateway Provided
- Weatherproof NEMA4 aluminum or NEMA4X stainless steel enclosure
- Silicon, cord grips and weatherstripping and LEXAN face

Contact EDI for more details: 1-800-367-6056 | [ledsales@electronicdisplays.com](mailto:ledsales@electronicdisplays.com)

135 S. Church Street Addison, Illinois 60101

## Electrical Specifications

Power Source	120VAC @ 60Hz. / 220VAC @ 50Hz.
Power Consumption	Max. 12 Watts
Current Draw	Typical 700 mA
Power Cord Length	10 Foot Business Plug

## Operation Specifications

Data input	Serial RS232 / RS422
Communication	Standard ASCII Protocol

## Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed <b>outdoor</b>
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	30.25"H x 10.25 W x 5"D for N4 and N4X Enclosures
Weight	NEMA4 - Approx. 18 Lbs.   NEMA4X – Approx. 37 lbs.
Number of Characters	Font and Size Dependent
Character Height	1.2" / 2.0" / 4.4" High Text
Viewing Distance	From 50 to 190 Feet Away (Character Size Dependent)
LED Color / LEXAN Face	Red or Amber / Bronze LEXAN Face
LED Intensity	1000 MCD Super-Bright LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA4 or NEMA4X Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service