ELECTRONIC DISPLAYS INC.

www.electronicdisplays.com



ED225-114- Common Weights



This four-digit model receives a customer supplied BCD input and displays it. Weights 1, 2, 4 and 8 are common for all four digits. "Common" and strobes are isolated (five wires per digit).

- Dimensions: 12"L x 4"H x 2.25"D
- 2.25" High Numbers!
- This four-digit model receives a customer supplied BCD input and displays it. Weights 1,
 2, 4 and 8 are common for all four digits. "Common" and strobes are isolated (five wires per digit).

Contact EDI Today

For further information visit our website <u>www.electronicdisplays.com</u> or call us at 1-800-367-6056 and contact a sales representative.

Henry Bilitzki x 305 | Dennis Holmberg x 306

Or email us at ledsales@electronicdisplays.com

ED225-114 Specifications

Electrical Specifications

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 15 Watts
Current Draw	Typical 500 mA
Power Cord Length	6 Foot Business Plug

Physical Specifications

Indoor / Outdoor	Designed to be installed and viewed indoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	12" L x 4" H x 2.25" D
Weight	Approx. 6 Lbs.
Number of Digits	Four (4) Digits
Character Height	2.25" High Numbers
Viewing Distance	Up to 100 Feet Away
LED Color / Material	Red
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service