

www.electronicdisplays.com



# ED1200-E-117-3D-N4-AM



Visible up to 575 feet Outdoor, 3- digit, Dimensions: 46" L x 21.25" H x 3" D. Display real-time

production information to your employees or customers. The display will receive an

RS422/RS485 data signal from a PC / PLC and update the unit using standard ASCII protocol.

- Visible up to 575 feet
- RS485 Serial Input using Standard ASCII Characters
- Dimensions: 46" L x 21.25" H x 3" D
- Terminal Block to Wire in Two Customer Supplied Contacts (RX+/RX-)
- Mounting Brackets
- Factory Service One-Year Warranty on Parts and Labor
- Unlimited Technical Phone Support

#### **Contact EDI Today**

For further information visit our website <u>www.electronicdisplays.com</u> or call us at 1-800-367-6056 and contact a sales representative. **Henry Bilitzki x 305 | Dennis Holmberg x 306** Or email us at ledsales@electronicdisplays.com

## ED1200-E-117-3D-N4-AM Specifications

### **Electrical Specifications**

Power Source	120VAC @ 60Hz.
Power Consumption	Max. 25 Watts
Current Draw	Typical 900 mA
Power Cord Length	6 Foot Business Plug

### **Physical Specifications**

Indoor / Outdoor	Designed to be installed and viewed outdoor
Operating Environment	32 to 120 Degrees (0 to 49 Degrees C) / 0 to 95% Humidity
Dimensions	46" L x 21.25" H x 3" D
Weight	Approx. 50 Lbs.
Number of Digits	Three (3) Digits
Character Height	12.0" High Numbers
Viewing Distance	Up to 575 Feet Away
LED Color / Material	Red, Green, Amber
LED intensity	10 MCD Super-Bright Discrete LEDS
Power Supply	Yes
Enclosure Color / Material	Black Aluminum
Enclosure NEMA Rating	NEMA 1 Rated
	NEMA 12 Rated
	NEMA 4 Rated
	NEMA4X Rated
Mounting Method	Two Mounting Brackets Included for Hanging / Wall Mount
Limited Warranty	One-Year Factory Service